



# MARTINI®

Weighing and packaging solutions

series

## MX800/1000/1200



**2B5K**



**GRANULAR PRODUCTS  
PASTA, RICE.  
SNACKS DRY  
FRUIT CANDIES  
COFFE GRAINS  
PET FOOD  
POWDER PRODUCTS**



CONFEZIONATRICI VERTICALI PER CATERING Mod. **MX800/1000/1200** ABBINATA A PESATRICE LINEARE **2B5K**  
VERTICAL BULK PACKAGING MACHINE Mod. **MX800/1000/1200** COMBINED WITH LINEAR WEIGHER **2B5K**

<b>CARATTERISTICHE / SPECIFICATIONS</b>					
<b>CONFEZIONATRICE MODELLO / VFFS MODEL</b>			<b>MX800</b>	<b>MX1000</b>	<b>MX1200</b>
PRODUZIONE MAX* FINO A / MAX RUNNING SPEED* UP TO			50 BPM *	40 BPM *	30 BPM *
DIMENSIONI BUSTA BAG SIZE	BUSTA A CUSCINO / PILLOW BAG	LARGHEZZA / WIDTH	MAX 380 mm	MAX 480 mm	MAX 580 mm
		LUNGHEZZA / LENGHT	MAX 650 mm	MAX 650 mm	MAX 650 mm
	FONDO QUADRO / FLAT BOTTOM BAG		MAX 290 x 90 mm	MAX 350 x 130	MAX 430 x 150
DIMENSIONI FILM FILM SIZE	DIAMETRO MAX BOBINA / MAX ROLL OUTER DIAMETER		400 mm		
	LARGHEZZA MAX BOBINA / MAX ROLL WIDHT		800 mm	1000 mm	1200 mm
	FORO SU BOBINA / BORE OF FILM ROLL CORE		Ø min 70 – Ø max 80		
CARATTERISTICHE FILM / FILM FEATURES		VERSIONE STANDARD : SOLO FILM IN PP LAMINATI O COESTRUSI STANDARD VERSION : ONLY LAMINATED OR COEXTRUDED PP			
PRODOTTO PRODUCT	PRODOTTI GRANULARI (PASTA, RISO, SNACKS, FRUTTA SECCA, CARMELLE, CAFFE' IN GRANI, CIBO PER ANIMALI ECC.) – POLVERI GRANULAR PRODUCTS ( PASTA, RICE, SNACKS, DRY FRUIT, CANDIES, COFFEE GRAINS, PET FOOD ETC.) – POWDER PRODUCTS				
MOVIMENTO FILM / FILM FEEDING MOTION			INTERMITTENTE / INTERMITTENT		
DIMENSIONI MACCHINA MACHINE SIZE	LARGHEZZA / WIDTH		1550 mm	1750 mm	1950 mm
	ALTEZZA / HEIGHT		2210 mm	2460 mm	2950 mm
	PROFONDITA' / LENGTH		2135 mm	2420 mm	2420 mm
POTENZA INSTALLATA / INSTALLED POWER			6 Kw	10 Kw	10 Kw
ALIMENTAZIONE ARIA / AIR SUPPLY			6 BAR / 200 NL/ 1' (max)	6 BAR / 250 NL/ 1' (max)	6 BAR / 250 NL/ 1' (max)
SOGLIA DI RUMOROSITA' / ENVIRONMENTAL NOISE LEVEL (TARGET)			MENO DI 80dB LOWER THAN 80dB		
PESO NETTO / NET WEIGHT			1000 Kg	1250 Kg	1350 Kg
TEMPERATURA DI ESERCIZIO / OPERATIONAL TEMPERATURE			5 – 45 °C		
ACCESSORI / OPTIONS	TIMBRATORE – KIT SALDATURA AD IMPULSO – MANICO A 3 FORI - FONDO QUADRO- INIEZIONE GAS – DATE PRINTER – IMPULSE SEALING JAWS KIT- 3 HOLES HANDLE - FLAT BOTTOM DEVICE – AIR NITROGEN INIECTION DEVICE				
<b>PESATRICE LINEARE MODELLO / LINEAR WEIGHER MODEL</b>				<b>2B5K</b>	
CARATTERISTICHE PRINCIPALI / MAIN FEATURES			ADATTA PER PESATE FINO A 5 ÷ 10 Kg. SUITABLE FOR WEIGHING UP TO 5 ÷ 10 Kg .		
NUMERO TESTE / HEADS NUMBER			2		
PRODUZIONE* / RUNNING SPEED*			FINO A 30 WPM** / UP TO 30 WPM**		
POTENZA INSTALLATA / INSTALLED POWER			2 Kw		
PESO NETTO / NET WEIGHT			1180 Kg		
TEMPERATURA DI ESERCIZIO / OPERATIONAL TEMPERATURE			5 – 45 °C		
ACCESSORI / OPTIONS	STAMPANTE - LAMIERA BUGNATA – SUPPORTO DI SOSTEGNO - TERRAZZA DI ISPEZIONE PRINTER - DIMPLED STEEL EXECUTION – SUPPORT STRUCTURE – INSPECTION TERRACE				
<p>* VALORI INDICATIVI RIFERITI A CONDIZIONI OTTIMALI DI IMPIEGO, CON L'UTILIZZO DI FILM ACCOPPIATI: LA VELOCITA' MAX RAGGIUNGIBILE DIPENDE DALLE CARATTERISTICHE DEL PRODOTTO, DAL PESO IMPOSTATO, DALLE DIMENSIONI DEL PACCHETTO, DAL FILM DI IMBALLAGGIO E DA UNA CORRETTA ALIMENTAZIONE</p> <p>* INDICATIVE VALUES REFERRED TO OPTIMALS WORK CONDITIONS, WITH THE USE OF COUPLED FILMS: MAXIMUN RUNNING SPEED IS SUBJECT TO CHANGE DEPENDING UPON THE PRODUCT,WEIGHT, BAG DIMENSION, PACKAGING MATERIAL AND IN-FEED CONDITION OF THE PRODUCT.</p> <p>** VALORI INDICATIVI RIFERITI A CONDIZIONI OTTIMALI DI IMPIEGO</p> <p>** INDICATIVE VALUES REFERRED TO OPTIMALS WORK CONDITIONS</p>					



**MARTINI**<sup>®</sup>  
weighing and packaging solutions

Martini s.r.l. via Borgo 21 35015 GALLIERA VENETA (PD) ITALY  
ph. +39 049 947 0600 - fax +39 049 596 8866  
info@martinisrl.com  
www.martinisrl.com